

XP series

Mid-size flexible proportional joystick •
non-contacting Hall effect technology



DISTINCTIVE FEATURES

- One or two axis
- Dual and dual inverse analogue and PWM outputs
- CAN J1939 & CANOpen
- All metal mechanism construction



ENVIRONMENTAL SPECIFICATIONS

- Operating Temperature: -30 °C to +70 °C (-22 °F to 158 °F)
- Storage Temperature: -40 °C to +85 °C (-40 °F to 185 °F)
- Sealing: IP66 (above panel subject to handle and final specification)
- EMC Immunity Level: EN61000-4-3 (exceeds)
- EMC Emissions Level: EN61000-6-3:2001, CPSPR 32:2015, Class B 30 MHz-1GHz
- ESD: EN61000-4-2 (exceeds)



ELECTRICAL SPECIFICATIONS

- Analog output Voltage Range: $\pm 10\% \times V$ to $\pm 50\% \times V$
- Output at Center: $V/2 \pm (5\% \times \text{gain})$
- Power Supply: 5 V ± 0.5 V transient free; 3.3 V ± 0.1 V
- Output impedance: 10 Ω
- Overvoltage max: +20 V



MECHANICAL SPECIFICATIONS

- Break out force: 3-5 N (subject to handle)
- Operating force: up to 12 N (subject to handle)
- Maximum force: Subject to handle
- Maximum Vertical Load: 1000 N (225 lbf) (subject to handle)
- Mechanical Angle of Movement: $\pm 17.5^\circ$ X & Y axis (subject to limiter)
- Expected Mechanical Life: 10 million cycles
- Mass/weight: 500 g (17.64 oz) nominal

The company reserves the right to change specifications without notice.



XP series

Mid-size flexible proportional joystick • non-contacting Hall effect technology



BUILD YOUR PART NUMBER

JOYSTICK BASE

XP

SERIES

CONFIGURATION

GAIN

LIMITER

01	Standard
02	3.3V Operation
03	Dual Outputs
04	Inverse Dual Outputs
05	PWM**
06	CAN**
07	CANopen**

10	±10%xV
25	±25%xV
30	±30%xV
40	±40%xV**
50	±50%xV

A	Single Axis NS	
B	Single Axis EW	
C	Cross	
R	Round	
S	Square	

SPRING FUNCTION

01	Standard spring to center
----	---------------------------

BEZEL

0	Below Panel***
6	Drop square bezel

GUIDED FEEL

20	Guided feel
----	-------------

TERMINATION

01	Standard central
02	Standard right angle

Custom cables available on request

HANDLE

AQ	Tall aluminium anodised
AR	Tall aluminium anodised with IA P/B
UR	Upright handle*
MF	Multifunction handle*

NOTES:

*Part number continues on next pages


**For configuration options 05, 06, and 07 40% gain is the default

****Not available with left or right side features


Mid-size flexible proportional joystick • non-contacting Hall effect technology



HANDLE OPTIONS



HANDLE	AQ	AR
MATERIAL	Aluminium	Aluminium
FINISH	Anodized	Anodized
STANDARD COLOR	Black	Black
NOTES		Uses APEM IA switch
SEALING	IP66	IP66
MAX HORIZONTAL LOAD	TBC	TBC
MAX Z LOAD	3Nm	3Nm




HANDLE	UR	MF
MATERIAL	Reinforced nylon	Reinforced nylon
FINISH	Anodized	Texture
STANDARD COLOR	Black	Black
SEALING	IP66	IP66
MAX HORIZONTAL LOAD	TBC	TBC
MAX Z LOAD	5Nm	5Nm

XP series

Mid-size flexible proportional joystick •
non-contacting Hall effect technology



BUILD YOUR PART NUMBER (continued)



NOTES:

* Standard option is a black HR series, single tab, 40% gain, single output. Many other options available (see APEM HR datasheet)

** Standard option is a black FNR series, no marking, MOM-OFF-MOM. Many other options available (see APEM FNR datasheet)

***HE6B are wired with 1 x N/O contact, the contact is closed in its mid position only. For disparity detection of two contacts please contact APEM. HE6B is not available with side configured options.


XP series

Mid-size flexible proportional joystick • non-contacting Hall effect technology


TOP FRONT SWITCH



X None




- 2 Black
- 3 Green
- 5 Yellow
- 6 Red
- B Blue




PERSON PRESENT




X None





- 1 IDEC HE6B yellow
- 2 IDEC HE6B black



LEFT OR RIGHT SIDE FEATURES




X None




XP series

Mid-size flexible proportional joystick • non-contacting Hall effect technology


R Right side features for left hand




L Left side features for right hand




SIDE CONFIGURATION




SXXX No switches




S001 HR series



S002 FNR series mom-off-mom




S003 1 x IX series



XP series

Mid-size flexible proportional joystick • non-contacting Hall effect technology

S004 4x IX series



TOP PLATE

UR

X


X

X


SXXX




TXXX No switches




T001 HR series



T002 FNR series mom-off-mom




T003 IX series




XP series

Mid-size flexible proportional joystick •
non-contacting Hall effect technology

T004 4 x IX series





Custom options available please contact APEM for
further details.



Mid-size flexible proportional joystick • non-contacting Hall effect technology



BUILD YOUR PART NUMBER (continued)



NOTES:

* Standard option is a black FNR series, no marking. Many other options available (see APEM FNR datasheet)

** Standard option is a black HR series, single tab, 40% gain, single output. Many other options available (see APEM HR datasheet)

*** Only available without faceplate trim, not compatible with R003 or R004


XP series

Mid-size flexible proportional joystick • non-contacting Hall effect technology


PERSON PRESENT



X No trigger



2 Black trigger



FACEPLATE TRIM



N1 Blue RAL 5012



N2 Black RAL 9011



N3 Green RAL 7044



XP series

Mid-size flexible proportional joystick •
non-contacting Hall effect technology

N4 Grey RAL 7044



N5 Yellow RAL 1023



N6 Red RAL 3031



N7 White RAL 1014



N9 Orange RAL 2009



XP series

Mid-size flexible proportional joystick •
non-contacting Hall effect technology


FACEPLATE

MF


X

N2


FXXX No switches




F001 1 x IX series




F002 2 x IX series




F003 3 x IX series




F004 4 x IX series




F005 5 x IX series



F006 6 x IX series




F007 1 x FNR series




F008 1 x FNR series +
2 x IX series




F009 1 x HR series
horizontal




F010 2 x HR series
vertical



F011 1 x HR series +
3 x IX series



Custom options available




XP series


Mid-size flexible proportional joystick • non-contacting Hall effect technology




RXXX None




R001 1 x IX series




R002 2 x IX series




R003 1 x FNR series
ON-OFF-ON



R004 1 x FNR series
MOM-OFF-MOM




Custom options available




XP series

Mid-size flexible proportional joystick •
non-contacting Hall effect technology

TERMINATION - STANDARD CENTRAL



TERMINATION - STANDARD RIGHT ANGLE





Mid-size flexible proportional joystick • non-contacting Hall effect technology



MOUNTING



When mounting the joystick, consideration should be given to the position so that unnecessary risk of damage is minimised. If the joystick is intended for use in a mobile enclosure then care must be taken to protect the joystick from damage caused by dropping. Basic precautions such as mounting it at the lightest end of the enclosure so it doesn't hit the ground first or by protecting it with a guard should always be implemented for long term reliability.

DROP-IN MOUNT CUT-OUT AND INSTALLATION BEZEL OPTION 6



- The joystick is dropped into the panel cut-out.
- Supplied with M5 low profile cap head bolts, spring washers and nuts. Must be torqued to 0.7 Nm
- When mounted this way the gaiter forms part of the panel seal however an addition seal is provided to ensure good bezel to panel contact.

UNDER PANEL MOUNT CUT-OUT AND INSTALLATION BEZEL OPTION 0



- When mounted this way the panel acts as the bezel and no separate bezel is needed.
- Supplied with sealed M5 screws spring washers and nuts. Must be torqued to 0.7 Nm
- When mounted this the upper part of the gaiter forms part of the panel seal, however an addition seal is provided to ensure good bezel to panel contact.

NOTES:

1. Dimensions are in mm/(inch).
 2. The dimensions shown are for XP AR handle. For specific dimensions of this or any other configuration please refer to APEM.
 3. When sub panel mounting, great care should be taken not to damage the boot, or any of the mechanism under the boot.
- All panel cut-outs should be free from sharp edges and debris that may damage the boot.

XP series

Mid-size flexible proportional joystick • non-contacting Hall effect technology



CONNECTIONS


The analogue and PWM joysticks are fitted as standard with 180mm(+/- 20mm) harnesses. Terminated to a 26 way housing TE 1-1827863-3.

Non standard connectors can be fitted upon request.

EXAMPLE WIRING TABLE		
TE CONNECTIVITY 1-1827863-3 PINOUT		
PIN	COLOUR	FUNCTION
A1	RED	+VA
B1	BLACK	OVA
A2	RED	+VB
B2	BLACK	OV B
A3	BLUE	X Axis A
B3	YELLOW	Y Axis A
A4	BROWN	X Axis B
B4	WHITE	Y Axis B
A5	GREEN	Z Axis A
B5	ORANGE	Z Axis B
A6	GREEN	Centre Tap
B6	ORANGE	Centre Detect
A7	ORANGE	Switch Common
B7	BLUE	Front Switch
A8	RED	Enable Switch Common
B8	RED	Enable Switch Normally Open
A9	RED	Enable Switch Normally Closed
B9	GREEN	Handle Function 1
A10	BLUE	Handle Function 2
B10	ORANGE	Handle Function 3
A11	GREEN	Handle Function 4
B11	BLUE	Handle Function 5
A12		
B12		
A13		
B13		

CONNECTOR DETAIL

26 way housing TE 1-1827863-3



WIRE SIDE




MATERIALS

- Shaft: Stainless steel
- Boot: Neoprene
- Body: Zinc
- Handles:
AR & AQ - Anodised aluminium
- UR: Reinforced Nylon
- MF: Reinforced Nylon



TERMINATION (CAN OUTPUTS ONLY)

- The XP series CAN options are supplied with 200mm harness terminated with an industrial connector.
- Connector detail: DTM04-6P



PIN	Connection	Colour
1	CAN LO	White
2	CAN HI	Green
3	ID LSB	Blue
4	ID MSB	Yellow
5	0V	Black
6	+12V	Red

Mid-size flexible proportional joystick • non-contacting Hall effect technology



CAN J1939 INTERFACE SPECIFICATION

The XP Series CAN options data is delivered on a CAN 2.0B compliant physical interface. Two additional signals allow configuration of the controller Source Address. Controller messages are delivered per the SAE J1939-71 message protocol.

CAN 2.0B INTERFACE PARAMETERS

- Baud rate: 250 kbps
- Transmission repetition rate: 50ms
- BJMI/EJMI interval time: 20ms
- Terminating resistor: No



CANopen INTERFACE SPECIFICATION

- Baud rate: 250 kbps
- Node ID: 20h
- Buttons: 1A0H (180H + NODE ID)
- Analog (axis) outputs: 2A0h (280h + Node ID)
- Heartbeat (500ms): 720h (700h + Node ID)
- Axis resolution: 8 bit
- Network Management: Auto start enabled


XP series

Mid-size flexible proportional joystick • non-contacting Hall effect technology




VOLTAGE OUTPUT OPTIONS



SINGLE OUTPUT - CONFIGURATION 1



DUAL OUTPUT - CONFIGURATION 3



DUAL OUTPUT - CONFIGURATION 4



Mid-size flexible proportional joystick • non-contacting Hall effect technology



CONFIGURATION

POWER SUPPLY

The analogue XP series is designed to be powered by a regulated $5V \pm 0.5V$ power supply. The outputs are ratiometric, making a stable, noise free, power supply essential.

MAGNETIC IMMUNITY AND SYSTEM DESIGN

The XP series incorporates internal magnetic screening to minimise the effect of external magnetic fields. Mounting or operating the joystick close to strong magnetic fields is not recommended. System designers should follow best practice when incorporating the XP series joystick into their products.

Care should be taken to decouple the power supply properly and to employ adequate EMC shielding.

CENTER DETECT (CD)

Where selected, (configuration 1 types) the output on this additional cable will be 0V while the joystick is inactive. Should either the X or Y outputs change outside of the centre tolerance, indicating that the joystick has been operated, the centre detect signal will switch to 5 V.

Within the joystick this output is pulled high by a 2K2 resistor and is decoupled by a 100 nF capacitor to 0 V.

This output is designed for use in applications requiring an enable/disable signal that is separate from the main X, Y outputs. It is not recommended for use as a safety feature or a method of "person-present" detection.

CENTER TAP REFERENCE (CT)

Where selected, (configurations 1, 3 and 4) the joystick also outputs a centre reference voltage that is set at 50% ($\pm 1\%$) of the supply voltage.

This output can be used to check the integrity of the power supply applied to the joystick. A reading on this output, outside of the specified tolerance suggests a problem with the power supply to the joystick.

The other purpose of this output is to act as a reference equal to the voltage output when the lever is at centre.

Measuring the voltage outputs relative to CT rather than 0 V eliminates inaccuracies created by variation in supply voltage.

GAIN OPTIONS

The voltage output on the HE outputs, at full scale deflection is determined by the gain. The gain is expressed as a percentage of the voltage supplied. Therefore (assuming a 5V supply) a joystick specified with $\pm 25\%$ gain would yield 1.25 V at South, 2.5 V at centre and 3.75 V at North.

A range of gain options are available as standard for configurations 01, 03 and 04. For output options 05, 06 and 07, 40% gain is the default specification. All joysticks are supplied pre-set and no further calibration is needed throughout the lifetime of operation.

OUTPUT IMPEDANCE

The voltage outputs at centre and at each end of travel are specified across an infinite load, with no current flowing.

The output impedance specified in the electrical specification should be taken into account when designing a system. Load resistance of less than 10 K Ohms is not recommended.

MECHANISM

The omni-directional mechanism utilises an extremely robust ball-socket pivot. This construction yields an end product that is extremely resistant to vertical impact.

Furthermore, it constantly withstands high pull, push, rotational or horizontal forces that the product may be subject to, during life.

SPRINGING

All XP series are offered sprung to centre. The standard spring force requires 3 – 5N to off-centre the joystick.

GUIDED FEEL

The XP series is supplied as standard with guided feel. A joystick with guided feel moves more readily towards the poles (N, S, E and W) and whilst it can still move away from the poles, the force required to do so is greater. For non-guided feel please contract APEM for availability.

EXTERIOR COMPONENTS

APEM has a huge range of control components, and only some basic options have been included in the standard XP configuration. Many other options are available as a custom XP configuration, refer to individual component datasheets for details.