

EMERGENCY STOP SWITCH SELECTION GUIDE

A01ES-D Series

- Panel Mount $\varnothing 16\text{mm}$
- IP65 panel sealed
- Certified to EN60947-5-5
- Push to shut-off, twist to release actuators
- Up to 2 pole positive break
- Contact rating AC-15 1.5A 250VAC / 6A 250VAC
- Five different prominent actuators
- Operating temperature -20°C to $+55^{\circ}\text{C}$
(-4°F to $+131^{\circ}\text{F}$)



A02ES-I Series

- Panel mount $\varnothing 22\text{mm}$
- Panel sealed up to IP65
- Certified to EN60947-5-5
- Push to lock / pull or twist to release actuators
- Up to 3 poles
- Contact rating AC-12, 3A 240VAC / DC-12, 8A 24VAC
- Mechanical life: 250,000 cycles with one contact block
- Illuminated model available



ES Series

- Panel mount $\varnothing 22\text{mm}$ (2pole) & 28mm (3 pole)
- Customizable anodized metal actuator
- Push/Pull ON/ON function
- Locked/unlocked status indicator
- Up to 3 poles
- Sealed up to IP69K
- IK10 impact resistant
- NC and NC/NO options
- Mechanical life: 100,000 cycles



A02ES-H Series

- Panel mount $\varnothing 22\text{mm}$
- Panel sealed up to IP65
- Certified to EN60947-5-5
- Push to lock / pull or twist to release actuators
- 2 pole NC + 1 pole NO
- Contact rating AC-12, 3A 250VAC / DC-12, 2A 30VDC
- Mechanical life: 250,000 cycles with one contact block
- Illuminated model available





INDUSTRIAL CONTROL SWITCH SELECTION GUIDE

A01 Series Pushbuttons & Indicators

- Panel mount \varnothing 16mm
- Rectangle, square & round bezels
- Up to 4 pole changeover
- Contact rating 6A 250VAC
- Sealed up to IP65, rear panel IP40
- 6VDC to 48VDC LEDs, bi-color options
- LED - 60,000 hours to 75% relative luminosity



A01 Series Keylocks & Selectors

- Panel mount \varnothing 16mm
- Panel sealed up to IP65
- Up to 4 pole changeover
- Contact rating 6A 250VAC
- Non-removable key positions
- Maintained & momentary functions



A1 Series - Aluminum Pushbuttons & Indicators

- Panel mount \varnothing 22mm
- Panel sealed up to IP65
- Up to 4 pole changeover
- Contact rating 6A 250VAC
- 6VDC to 48VDC LEDs, bi-color options
- Engraved screens or legend inserts
- LED - 60,000 hours to 75% relative luminosity



A02 Series Pushbuttons & Indicators

- Panel mount \varnothing 22 or \varnothing 30mm
- Panel sealed up to IP65
- Contact rating 16A 250VAC
- Latching & momentary functions
- 6VDC to 48VDC LEDs, bi-color options
- Engraved screens or legend inserts
- LED - 60,000 hours to 75% relative luminosity



A02 Series Keylocks & Selectors

- Panel mount \varnothing 22 or \varnothing 30mm
- Panel sealed up to IP65
- Custom engraving & molded key
- Non-removable key positions
- Maintained & momentary functions
- Contact rating 16A 250VAC



A03 Series Pushbuttons & Indicators

- Panel mount \varnothing 22 or \varnothing 30mm
- Panel sealed up to IP65, rear panel IP40
- Latching & momentary functions
- Contact rating 6A 250VAC
- 6VDC to 48VDC LEDs, bi-color options
- LED - 60,000 hours to 75% relative luminosity



A3 Series - Aluminum Pushbuttons & Indicators

- Panel mount \varnothing 30mm
- Panel sealed up to IP65
- Up to 4 pole changeover
- Latching & momentary functions
- Chemically etched aluminum screens or polyester inserts
- Contact rating 6A 250 VAC
- Illuminated



LK Series Keylocks

- Panel mount \varnothing 19mm
- 5 tumbler single sided bitted key
- 1 or 2 pole options, 4 positions
- Overmolded key option
- Maintained & momentary functions
- 45° or 90° indexing with multiple key pull positions

