

EMERGENCY STOP SWITCH SELECTION GUIDE

A01ES-D Series Compact modern design

- Panel Mount Ø16mm
- IP65 panel sealed
- Certified to EN60947-5-5
- Twist to release actuators
- Up to 2 pole positive break
- Contact rating 6A 240VAC
- 5 different prominent actuators
- Operating temperature -20° C to +55° C



ES Series Heavy duty

- Panel mount Ø22mm
- IP69K panel sealed
- 100,000 cycles
- PCB or solder lug terminals
- IK10 impact
- Push/Pull



A02ES-H Series High security, fail safe construction

- Panel Mount Ø22mm
- · IP65 panel sealed
- Terminals IP20 (finger safe)
- Pull or twist to release actuators
- Certified to EN60947-5-5. EN60547-5-1 UL508 and CSA
- Up to 2 pole positive break + single pole normally open
- Contact rating AC-12, 3A 250VAC / DC-12, 2A 30VDC
- Operating temperature -25° C to +60° C



A02ES-I Series Compact modern design

- Panel Mount Ø22mm
- IP65 panel sealed
- Certified to EN0947-5-5
- Twist to release actuators
- Up to 2 pole positive break
- Contact rating 6A 240VAC
- Illuminated actuator option
- Operating temperature -20° C to +55° C







INDUSTRIAL CONTROL SWITCH SELECTION GUIDE

A01 Series Pushbutton & indicators

- Panel Mount Ø16mm, IP65 sealed
- · Rectangular, square, round bezels
- Up to 4 pole changeover
- Contact rating 6A 240VAC
- LED's 6VDC to 48VDC
- Bi-colour options





A01 Series Keylocks & Selectors

- Panel Mount Ø16mm
- IP65 panel seal
- Maintained & momentary functions
- Up to 4 pole changeover
- Contact rating 6A 240VAC
- Non- removable key positions



A1 Series - Aluminium Pushbutton & indicators

- Panel Mount Ø22mm, IP65 panel seal
- Up to 4 pole changeover
- LED's 6VDC to 48VDC
- Bi-colour options
- Aluminium chemically etched screens or polyester inserts





A02 Series Pushbutton & indicators

- Panel Mount Ø22 or 30mm
- IP65 panel sealed
- · Latching & momentary functions
- Contact rating 16A 240VAC
- LED's 6VDC to 48VDC + Bi-colour options
- Engraved screens or legend inserts





A02 Series Keylocks & Selectors

- Panel Mount Ø22 or 30mm
- IP65 panel sealed
- Maintained & momentary functions
- Contact rating 16A 240VAC
- Non- removable key positions
- Custom moulded key

A03 Series Pushbutton & indicators

- Panel Mount Ø22 or 30mm
- IP65 panel sealed
- Latching & momentary functions
- Contact rating 6A 240VAC
- LED's 6VDC to 48VDC

or supply is interrupted

• Bi-colour options





A3 Series - Aluminium **Pushbutton & indicators**

- Panel Mount Ø30mm
- IP65 panel sealed
- Latching & momentary functions
- Up to 4 pole changeover
- Aluminium chemically etched screens or polyester inserts

306 Series Stop/Start pushbutton Switch with low volt release and emergency

stop auxiliary input. Power is reset to off if E-stop switch is activated



LK Series Keylocks

- Panel Mount Ø19mm
- 5 tumbler single sided bitted key
- Maintained & momentary functions
- Up to 4 pole positions
- Overmoulded key option







PANEL SWITCHES

PCB SWITCHES

JOYSTICKS

SWITCH PANELS

